

MODEL : ZSA6363 – 80M1GA

- Class A Solid state
- Broadband(Instantaneous Single Band)
- Linear Output Power
- Low Distortion
- Internal Systems Diagnostics and Status Indicator
- Bench Case
- 3Years Standard Warranty

Built – In Protection

- High Temperature
- Supply Voltage
- FWD Over Power
- REF Over Power

Maintenance

- Amplifier Designed For Minimal Maintenance
- Rapid Diagnostic
- Minimal Downtime

Applications


- EMC Tests
- RF Tests And Instrumentation
- Radio communication
- Measurement And Research Laboratories

Additional Options

- RF Connector Type
- RF Sample Port (Front or Rear Panel)
- Detected Sample Port (Front or Rear Panel)
- RF Input Switch
- Gain Control

Outline Drawing


※ In Millimeters



Specifications

• Frequency Bandwidth	80MHz - 1GHz
• Rated Output Power(1dB Gain Compression)	2kW CW (min)@80M~500MHz 1.8kW CW (min)@500M~1GHz
• Gain Compression	1dB(max) @Po= Rated Output Power ※1
• Class Type	Class A
• Gain	63dB (min)
• Gain Flatness	±3.5dB (max)
• Impedance	50ohms nominal
• Harmonics	-18dBc (max) @Po=Rated Output Power
• Spurious	-70dBc (max) @Po=Rated Output Power
• Input VSWR	2:1 (max)
• RF Input Connector	N-Female (Rear Panel)
• RF Output Connector	1_5/8" EIA (Rear Panel)
• Input Power	+3dBm (max)
• Operating Temperature	0°C - +35°C
• Room Temperature Storage	-20°C - +50°C
• Cooling	Forced Air (Self Contained Fans)
• Power Voltage	200-240VAC, 50 - 60Hz, Three Phase
• Rated Current	50A at 200VAC Three Phase
• Weight	350kg
• Dimensions	19"System Rack /EIA 30U (W)560×(D)1000×(H)1603.5 mm
• Safety Interlock	Connector Type BNC-Female
• REMOTE	IEEE488 Ethernet

Model ZSA6363-80M1GA Typical Power Output



※ Continual operation exceeded specified power-output may cause product damage.

※1 Indicates the output power level at which the specified gain compression occurs, referenced to the input level 10 dB below that at the measured output power.