

# 新高式強力アングルベンダー仕様 Specification of Nijitaka System Angle Benders

	(65型)	(75型)	(100型)	(130型)	(150型)	(200型)	(300型)
L 外曲 Outward bending of L	6 x 65 x 65	9 x 75 x 75	13 x 100 x 100	13 x 130 x 130	19 x 150 x 150	25 x 200 x 200	25 x 300 x 300
最小径 Minimum diameter	500	900	1,000	1,500	1,700	5,000	6,500
J 内曲 Inward bending of J	6 x 50 x 50	8 x 65 x 65	10 x 90 x 90	13 x 100 x 100	16 x 150 x 150	19 x 150 x 150	25 x 200 x 200
最小径 Minimum diameter	500	700	1,000	1,200	1,700	4,000	6,000
[ 内外曲 Outward bending of [	75 x 40	100 x 50	180 x 75	200 x 90	300 x 100	350 x 100	380 x 100
最小径 Minimum diameter	600	1,000	1,800	2,500	3,000	5,000	5,500
—	12 x 50	16 x 75	25 x 100	25 x 150	30 x 150	40 x 160	40 x 200
最小径 Minimum diameter	500	800	1,200	2,000	2,500	5,000	6,000
● G P	2"	2½"	3.5"	5"	6"	8"	10"
最小径 Minimum diameter	500	1,000	1,500	3,000	3,500	8,000	10,000
● ■	38	45	65	80	90	100	120
最小径 Minimum diameter	500	600	750	1,500	1,800	5,000	5,500
< >	6 x 50 x 50	8 x 65 x 65	10 x 90 x 90	13 x 100 x 100	13 x 130 x 130	19 x 150 x 150	25 x 200 x 200
最小径 Minimum diameter	900	1,000	2,000	2,500	3,500	5,000	8,000
Hアーチ曲 Bending of H to arch shape				125 x 125	150 x 150	200 x 200	350 x 350
最小R Minimum radius				2,500	3,000	8,000	12,000
∟アーチ曲 Bending of ∟ to arch shape				125 x 60	150 x 90	200 x 90	300 x 100
最小R Minimum radius				2,500	3,500	12,000	12,000
重量 Weight	1,500	2,800	3,500	7,500	11,500	15,000	25,000
ロール径 Diameter of roll	240	300	400	440	590	800	900
速度毎分 Speed/min.	9,000	8,000	8,000	8,000	8,000	8,000	8,000
電動機 KW Motor (KW)	3.7	7.5	11	15	22	30	37
全巾×長さ Overall width and length	1,200 x 1,200	1,500 x 1,700	1,700 x 1,900	2,100 x 2,200	2,450 x 2,600	2,800 x 3,900	3,300 x 4,500



NIJITAKA  
MADE IN JAPAN