

CONFIDENTIAL

Energy Management System (EMS)

DIASYS Netmation®



CONTENT

1

Energy management system

What is EMS & Features

2

Project references

Our success stories

Part . 1

Energy Management System




What is EMS & Features

Energy Management System

CONFIDENTIAL

A single system managing the whole factory utilities is the final goal of our expectation.


We offer the energy supply equipment essential to factory operation (electricity, steam, hot and chilled water, air conditioning) as “Energy Center” package, tailored to your needs.





Energy Management Development Cycle

CONFIDENTIAL





Manual Operation VS Energy Management system

CONFIDENTIAL

Production Requirement



Production Requirement



Man-Power



Pumps



Valves




Chillers



Cooling Towers


Energy Saving



Man-hour Lost



Report Handling



Alarm Response



Manual Operation VS Energy Management system

CONFIDENTIAL


Production
Requirement



Production
Requirement



Energy Management



Pumps



Valves



Chillers




Cooling
Towers

Energy Saving



Man-hour Lost



Report Handling




Alarm Response



Management Level is able to access to Energy Management System via Smart phones / Tablet / Notebook

- Access to operator screens
- Access to the energy report
- Access to the utility cost report




Features and Benefits

- Real-Time Utility's Cost Monitoring for each shops, each production lines
- Real-Time Machine Status Monitoring such as chillers, air compressors, and boilers
- Real-Time Machine's Efficiency Monitoring
- Waste/Loss Energy Monitoring
- Real-Time Trend Function Monitoring for operator
- Automatic Reporting
- Automatic Alarming
- Remote Monitor via Smart Phone
- Reduce OPEX for long-term maintenance
- Communication with the existing system (PLC, DCS, SCADA)

System Configuration Supply


CONFIDENTIAL



SOFTWARE MAIN FEATURES

Logic Modification


- ✓ Easy to expand, modify, upgrade ⇒ Reduction of cost
- ✓ No skill required (Function box language based on Microsoft VISIO)
- ✓ Modification, upgrade and expand are allowed



Window Layout Flexibility

Netmation focuses on the useful operability of monitoring and operation screens.

In Netmation, it is not necessary to fix monitors for some specific purpose. By mouse operation, the scalable structure of multiple-screens is available and saving of screen layout as "My favorite" is available.




Automatic Reporting

- ✓ Daily report and Monthly report
- ✓ Automatically printing able to be set

DATE	TIME	ITEM	VALUE	UNIT	ALARM	STATUS	REMARK
2011/11/11	10:00	101	10.0	MPa	OK	Normal	
2011/11/11	10:05	102	10.5	MPa	OK	Normal	
2011/11/11	10:10	103	11.0	MPa	OK	Normal	
2011/11/11	10:15	104	11.5	MPa	OK	Normal	
2011/11/11	10:20	105	12.0	MPa	OK	Normal	
2011/11/11	10:25	106	12.5	MPa	OK	Normal	
2011/11/11	10:30	107	13.0	MPa	OK	Normal	
2011/11/11	10:35	108	13.5	MPa	OK	Normal	
2011/11/11	10:40	109	14.0	MPa	OK	Normal	
2011/11/11	10:45	110	14.5	MPa	OK	Normal	


Event Alarm Detection

- ✓ Buzzer is included
- ✓ Alarming priority can be set




Trend display as Report

Netmation focuses on the sufficient usability to support monitoring and reporting work.
"Monitoring convenience" enables Operator to use screen image as report on paper.



Trend display as Report



Useful function (1)

- Many selections of background color, line color and line type
- Flexible scaling



Useful function (2)

Recent mode: displays real time data
Historical mode: displays historical data

Data collection cycle and time can be set as you like (according to storage capacity). **

Useful function (3)

Post-it and flag marking are included as standard. The flag can be set by drag & drop from alarm/event. The information traceability is upgraded.



**** Standard setting of each mode (It is settable according to storage capacity.)**

The standard data collection cycle and time of each mode (recent / historical) is as follows.

- Recent mode: 1-second cycle within 24 hours
- Historical mode: 10-second cycle, over 24 hours and up to 31 days



Part . 2

Project references



Our success stories

Success Stories – Yarn Manufacturer

CONFIDENTIAL



Yarn manufacturer factory



Electricity fee is able to change by customer

Visualize the efficiency compare with the standard & Running cost


Success Stories – Yarn Manufacturer

CONFIDENTIAL

06

Improvement of chiller system (Feb 2021)

- Replacement of 1 existing chiller with MHI high efficiency model (Fix)



04


Further Improvement (June 2016 to March 2018)

- Replacement of 1 existing chiller with MHI high efficiency model (VSD)

02

MHI Solution (May 2015)

- Automatic start and stop of Chillers and Aux. equipment by EMS considering factory demand



Air Com Efficiency Monitoring (March 2019)

- Efficiency monitoring and reporting
- Cost monitoring and reporting
- Loss monitoring

Effect of Improvement (May 2015 to March 2016)

- 10% of Energy Cost Saving with ROI: 2.5 year (EMS + Modification of valves and sensing devices)

Monitoring, Visualization & Analysis (Sep 2014)

- 3,300 RT (1,100 RT x 3 sets) Chilled System always operated in manual
- However, actual thermal demand is less than 2,000 RT

05

03

01

Success Stories – MSG Manufacturer

CONFIDENTIAL



MSG manufacturer factory

0°C LINE A-D			20°C LINE A-C			COP(Coefficient Of Performance)								
GROUP	DEVICE	POWER CONSUMPTION	GROUP	DEVICE	POWER CONSUMPTION	KC-N9513A	KC-N9513B	KC-N9513C	KC-N9513D	SYSTEM COP	KC-N9503A	KC-N9503B	KC-N9503C	SYSTEM COP
CHILLER	KC-N9513A	425.0 kW	CHILLER	KC-N9503A	0.0 kW	2.89	0.00	2.67	0.00	1.37	14399124...	0.00	0.00	15.42
	KC-N9513B	0.0 kW		KC-N9503B	0.0 kW	SYSTEM COP								
	KC-N9513C	361.1 kW		KC-N9503C	0.0 kW	14399124...								
	KC-N9513D	354.8 kW		PC-N9502A	51.2 kW	SYSTEM COP								
Br SENDING PUMP	PC-N9512A	109.4 kW	CHW SENDING PUMP	PC-N9502B	0.0 kW	14399124...								
	PC-N9512B	96.8 kW		PC-N9502C	0.7 kW	14399124...								
	PC-N9512C	37.3 kW		PC-N9502D	0.0 kW	14399124...								
	PC-N9512D	0.0 kW		PC-N9504A	18.0 kW	14399124...								
Br CIR. PUMP	PC-N9512G	104.9 kW	CW CIR. PUMP	PC-N9504B	23.4 kW	14399124...								
	PC-N9514A	33.3 kW		PC-N9504C	0.0 kW	14399124...								
	PC-N9514B	29.3 kW		PC-N9504D	0.0 kW	14399124...								
	PC-N9514C	13.3 kW		PC-N9504E	0.0 kW	14399124...								
TOTAL	PC-N9514D	40.4 kW	TOTAL		93.4 kW	INTEGRATING POWER CONSUMPTION								
	PC-N9514G	0.0 kW	TOTAL		1604.7 kW	REAL-TIME CALCULATION OF CHILLED WATER COST								
0°C LINE E-F			TODAY'S ELECTRICITY FEE			INTEGRATING POWER CONSUMPTION								
GROUP	DEVICE	POWER CONSUMPTION	TIME	ELECTRICITY FEE		GROUP	INTEGRATING POWER CONSUMPTION							
CHILLER	KC-N9513E	453.5 kW	ON PEAK TIME	4.1283 THB/kWh			0°C LINE (A-D)	TODAY THB	TODAY	THIS MONTH THB	THIS MONTH	LAST MONTH THB	LAST MONTH	
	KC-N9513F	0.0 kW	OFF PEAK RATE	2.6107 THB/kWh				CHILLER	28082 THB	9472 kWh	358793 THB	109983 kWh	0 THB	0 kWh
Br SENDING PUMP	PC-N9512E	14.7 kW	MAIN MENU		Br SENDING PUMP			2513 THB	3825 kWh	197836 THB	60012 kWh	0 THB	0 kWh	
	PC-N9512F	114.8 kW	SENDING PUMP CONTROL		Br CIR. PUMP	2513 THB		847 kWh	171971 THB	55671 kWh	0 THB	0 kWh		
Br CIR. PUMP	PC-N9514E	0.0 kW	CHILLER CONTROL		0°C LINE (E-F)	SUB TOTAL	41717 THB	14144 kWh	728599 THB	225686 kWh	0 THB	0 kWh		
	PC-N9514F	43.2 kW	CHILLER CONTROL SEQ.			CHILLER	12742 THB	4381 kWh	177971 THB	55510 kWh	0 THB	0 kWh		
TOTAL	626.3 kW		CHILLER CONTROL			Br SENDING PUMP	3682 THB	1329 kWh	63519 THB	19375 kWh	0 THB	0 kWh		
			CHILLER CONTROL SEQ.			Br CIR. PUMP	1361 THB	469 kWh	37868 THB	10494 kWh	0 THB	0 kWh		
CHILLER	KC-N9513E	453.5 kW	CHILLER CONTROL		20°C LINE (A-C)	SUB TOTAL	17985 THB	6179 kWh	279358 THB	85379 kWh	0 THB	0 kWh		
	KC-N9513F	0.0 kW	CHILLER CONTROL SEQ.			CHILLER	2639 THB	1011 kWh	11277 THB	3311 kWh	0 THB	0 kWh		
Br SENDING PUMP	PC-N9512E	14.7 kW	CHILLER CONTROL			CHW SENDING PUMP	732 THB	237 kWh	32570 THB	10480 kWh	0 THB	0 kWh		
	PC-N9512F	114.8 kW	CHILLER CONTROL SEQ.			CHW CIR. PUMP	993 THB	351 kWh	212390 THB	55140 kWh	0 THB	0 kWh		
Br CIR. PUMP	PC-N9514E	0.0 kW	CHILLER CONTROL		SUB TOTAL	4385 THB	1598 kWh	256236 THB	68931 kWh	0 THB	0 kWh			
	PC-N9514F	43.2 kW	CHILLER CONTROL SEQ.		TOTAL RUNNING COST	64047 THB	21921 kWh	1713434 THB	379976 kWh	0 THB	0 kWh			
TOTAL	626.3 kW		CHILLER CONTROL		INTEGRATING POWER CONSUMPTION									
			CHILLER CONTROL SEQ.		REAL-TIME CALCULATION OF CHILLED WATER COST									

Success Stories – MSG Manufacturer

CONFIDENTIAL

Modification of chiller system (Feb 2022)

- Add blackout function to chiller system Utilities 1 combination with new biomass power plant 9.9 MWe

06

Further Improvement (Jan 2019)


- Full auto control running
- Actual ROI: around 1.5 year

04

Chiller Optimization for Utilities 1 (May 2017)

- Automatic start and stop of Chillers and Aux. equipment by EMS considering factory demand
- Run priority chiller

02



Chiller Optimization for Utilities 2 (Dec 2021)

- Established EMS separately from Utilities 1

05

Support customer (Jun 2017 to Dec 2018)

- Equipment fixing consultation by MHI
- Valves and sensing devices modification
- Programming modification

03

Data Analysis (2016)




- 5 sets of chiller operation manner analysis.
- Chillers always operated in manual
- Actual thermal demand is less than 2,000 RT

01

Table: Production amount (ton) VS Energy consumption (kWh)

	Ton-Product (Monthly)				
	2015	2016	2017	2018	2019
Jan	4,098	4,077	2,818	4,187	4,253
Feb	3,633	3,915	2,334	3,799	1,481
Mar	4,019	3,941	4,223	3,691	4,246
Apr	3,993	4,013	4,161	3,544	4,218
May	4,129	4,184	2,553	3,968	4,065
Jun	3,932	4,030	2,328	4,093	3,934
Jul	3,949	4,196	3,799	4,171	4,320
Aug	4,112	4,252	4,072	4,063	4,019
Sep	3,892	4,120	3,977	3,963	4,042
Oct	4,012	4,202	4,313	4,089	4,094
Nov	2,072	4,061	2,748	4,110	4,107
Dec	4,079	4,270	4,393	3,995	3,669
Total	45,919	49,261	41,718	47,673	46,447
	93%	100%	85%	97%	94%

	kWh (Monthly) Total 10 + 20 degC				
	2015	2016	2017	2018	2019
Jan	568,665	522,259	413,921	505,190	531,426
Feb	401,378	600,412	350,807	566,765	272,305
Mar	606,226	571,385	531,808	616,486	494,380
Apr	694,847	775,615	542,325	523,200	530,050
May	706,691	1,069,806	383,508	605,181	554,181
Jun	480,830	1,048,676	366,137	649,976	497,440
Jul	606,653	813,472	547,597	674,590	407,790
Aug	616,909	783,315	578,732	665,292	414,430
Sep	585,872	959,973	562,600	697,687	435,930
Oct	606,820	939,549	545,946	510,593	452,850
Nov	369,801	786,437	373,450	543,918	361,880
Dec	557,249	577,754	508,672	524,364	567,510
Total	6,801,941	9,448,653	5,705,503	7,083,242	5,520,172
	72%	100%	60%	75%	58%



Product per Energy consumption calculation

Y2016 - 9,448,653(kWh) / 49,261 (Ton) = 191.8 (kWh/Ton)

Y2019 - 5,520,172(kWh) / 46,447 (Ton) = 118.8 (kWh/Ton)


Cost Saving.

$[191.8 \text{ (kWh/Ton)}] - [118.7 \text{ (kWh/Ton)}] \times 46,447 \text{ (Ton)} = 3.39 \text{ M [kWh]}$

*Electric tariff (Avg. 3.4 THB/kWh) = 11,521,490 THB/Year

CO₂ Saving.

*CO₂ Emission Reduction (Base 0.5642 kgCO₂/kWh) = 1,912,994 kgCO₂





Success Stories – Vehicle part Manufacturer

CONFIDENTIAL



Vehicle part manufacturer factory





Improvement of power monitoring (*Under designing*)

- Include Plant#1, Plant#3, Plant#6 to EMS.

04

Power monitoring system (June 2020)

- Established EMS for power monitoring Plant#2, Plant#5, Plant#7

02

New power meter installation (Apr 2021)

- Installed Plant#1, Plant#3, Plant#6 power meters and cable wiring.

03


Analysis for EMS (Nov 2019)

- First step for EMS, plant by plant monitoring
- Focused on the most energy usage plant

01


Success Stories – Tire Manufacturer

CONFIDENTIAL




Tire manufacturer factory

OVERVIEW AIR COMPRESSOR A - F



AIR COMPRESSOR PROCESS AND ALARM



04

Air compressor monitoring (Jan 2022)


- Efficiency monitoring and reporting
- Cost monitoring and reporting

02


Power monitoring system (Aug 2020)

- Established EMS for power monitoring the most consumer machine such Mixer.
- Peak-cut function alarm.

Forecast in each 15 minutes time slot is updated every minute, simply based on now and 5 minutes before data.



03




01

Air compressor monitoring (Apr 2021)

- Extended project for air compressor monitoring system

Analysis for EMS (2019)

- First step for EMS, power monitoring for Mixer machine.
- Customer problem is the fee of peak power charge is too high.



MOVE THE WORLD FORWARD

**MITSUBISHI
HEAVY
INDUSTRIES
GROUP**