

TUTELA MR 3 Cod. 1904

DESCRIPTION

Special multi-purpose lithium-based grease for the lubrication of heavy commercial vehicle wheel hub bearing and the general grease lubrication of heavy commercial vehicles which do not require a specific grease.

The product is a dark green colour and has a soft and stringy texture.

CHARACTERISTICS

- Excellent mechanical stability, keeps grease leakage to a minimum.
- Excellent anti-oxidant characteristics for improved lubricant endurance.
- High resistance to the water to withstand the fading action caused by water.
- High thermal stability for use in temperatures from -20°C to 120°C.

As it exceeds the strict quality requirements of the major European Manufacturers, TUTELA MR3 can be used in machinery of every make, type and power rating.

ADVICE ON USE

TUTELA MR3 is available in NLGI 3 grade.

For agricultural machinery replacement should be as indicated by the constructor; however, in any case every 50 hours. For industrial vehicles oil replacement should be as indicated by the constructor, in any case not beyond 50,000 km.

RECOMMENDED BY

FIAT, Lancia, Alfa Romeo, Iveco.

APPROVED BY

Piaggio.

TECHNICAL DATA

NLGI 3,
FIAT 9.55580 CONTRACTUAL TECHNICAL REF.N°F002.I90,
IVECO 18-1810 CLASSE I,CONTRACTUAL TECHNICAL REF. N°I002.I90



850 g