



Screwdriving technology

Automation

Air motors

Air tools

DEPRAG

MINIMAT

MINIMAT-Screwdrivers pistol-grip

from 0.3 - 20 Nm (3 to 177 in.lbs)

- **accurate**
- **ergonomic**
- **long life expectancy**
- **low noise level**

The pistol-grip screwdrivers are preferably used for horizontal screw assemblies.

The models with the prefix 347-..., are now available with an expanded torque range from 0.3 - 5 Nm (3 - 44 in.lbs). Those new pistolgrip drivers are smaller in size with a reduced weight. They incorporate advanced ergonomics and allow the possibility to choose between an air-inlet option from either below or from the top.

All design models incorporate the well-known characteristics of the MINIMAT-series, where the accuracy of the screwdriver is higher than any subsequent control method.

The preset torque remains constant, independent of hard- or soft pull-up joints and air pressure fluctuations.

The screwdriver is actuated by trigger. If needed, Exhaust Hoses can be connected to the screwdriver; this will direct exhaust air away from the assembly area. For size 3 pistol-grip drivers, we offer additional side-handles, which are an useful addition for higher torque values.



Motor size 3 and 4
(lower air-inlet)



Motor size 3 and 4
(upper air-inlet)



Motor size 3 and 4
(rear air-inlet)



Motor size 2
(lower air-inlet)



Motor size 2
(upper air-inlet)



Motor size 2,5
(lower air-inlet)



Technical Data

Screwdriver style			Motor size 2			
reversible, trigger-start lower air-inlet	type order no.		347-227 U 394569 A	347-327 U 394569 B	347-427 U 394569 D	347-527 U 394569 C
reversible, trigger-start upper air-inlet	type order no.		347-227 OU 394570 A	347-327 OU 394570 B	347-427 OU 394570 D	347-527 OU 394570 C
reversible, push-to-start lower air-inlet	type order no.		347-229 U 394573 A	347-329 U 394573 B	347-429 U 394573 D	347-529 U 394573 C
reversible, push-to-start upper air-inlet	type order no.		347-229 OU 394574 A	347-329 OU 394574 B	347-429 OU 394574 D	347-529 OU 394574 C
screws	up to		M3	M4	M4	M5
torque min.	Nm / in.lbs		0.5 / 5	0.4 / 4	0.4 / 4	0.3 / 3
torque (soft pull-up) max.	Nm / in.lbs		1.3 / 11	3 / 26	3.5 / 31	5 / 44
torque (hard pull-up) max.	Nm / in.lbs		1.5 / 13	3.2 / 28	4 / 35	5 / 44
speed, idling	rpm		3000	1100	750	500
air consumption	m³/min / cfm		0.3 / 11	0.3 / 11	0.3 / 11	0.3 / 11
distance from spindle centre to side	mm / in.		14,5 / ⁹ / ₁₆	14,5 / ⁹ / ₁₆	14,5 / ⁹ / ₁₆	14,5 / ⁹ / ₁₆
length	mm / in.		208 / 8 ³ / ₁₆	208 / 8 ³ / ₁₆	208 / 8 ³ / ₁₆	208 / 8 ³ / ₁₆
weight	kg / lbs		0.75 / 1.6	0.75 / 1.6	0.75 / 1.6	0.75 / 1.6
noise level	dB(A)		69	69	69	69

Screwdriver style			Motor size 2.5			
reversible, trigger-start lower air-inlet	type order no.		346-7257 U 412799 A	346-3257 U 412799 B	346-4257 U 412799 C	
reversible, push-to-start lower air-inlet	type order no.		345-7259 U 390854 A	345-3259 U 390854 B	345-4259 U 390854 C	
screws	up to		M5	M6	M6	
torque min.	Nm / in.lbs		1 / 9	1 / 9	1 / 9	
torque (soft pull-up) max.	Nm / in.lbs		5 / 44	10 / 88	12 / 106.2	
torque (hard pull-up) max.	Nm / in.lbs		6 / 53	10 / 88	12 / 106.2	
speed, idling	rpm		1025	525	270	
air consumption	m³/min / cfm		0.35 / 12	0.35 / 12	0.35 / 12	
distance from spindle centre to side	mm / in.		20 / ²⁵ / ₃₂	20 / ²⁵ / ₃₂	20 / ²⁵ / ₃₂	
length	mm / in.		240 / 9 ⁷ / ₁₆	240 / 9 ⁷ / ₁₆	240 / 9 ⁷ / ₁₆	
weight	kg / lbs		1.2 / 2.6	1.2 / 2.6	1.2 / 2.6	
noise level	dB(A)		72	72	72	

Screwdriver style			Motor size 3			
reversible, trigger-start upper air-inlet, lower air-inlet or rear air-inlet	type order no.		346-237 U 400373 B	346-737 U 400373 C	346-337 U 400373 D	346-437 U 400373 E
reversible, push-to-start upper air-inlet, lower air-inlet or rear air-inlet	type order no.		346-239 U 411447 B	346-739 U 411447 C	346-339 U 411447 D	346-439 U 411447 E
screws	up to		M5	M6	M6	M8
torque min.	Nm / in.lbs		2 / 17.7	2 / 17.7	2 / 17.7	2 / 17.7
torque (soft pull-up) max.	Nm / in.lbs		4.5 / 39.8	7 / 62	12 / 106.2	20 / 177
torque (hard pull-up) max.	Nm / in.lbs		5.5 / 48.7	8 / 70.8	12 / 106.2	20 / 177
speed, idling	rpm		2300	1200	650	320
air consumption	m³/min / cfm		0.4 / 14	0.4 / 14	0.4 / 14	0.4 / 14
distance from spindle centre to side	mm / in.		21 / 0.8	21 / 0.8	21 / 0.8	21 / 0.8
length	mm / in.		280 / 10.9	280 / 10.9	280 / 10.9	280 / 10.9
weight	kg / lbs		1.6 / 3.5	1.7 / 3.75	1.7 / 3.75	1.7 / 3.75
noise level	dB(A)		72	72	72	72

Performance data relate to an air pressure of 6.3 bar (90 PSI), Air hose dia. 6 mm/1/4", Internal hex. drive DIN 3126 – F6.3 (1/4"), integrated quick change chuck

Suitable tool inserts and connecting components with a drive as per DIN 3126 E6.3 (1/4"), see also in our brochure D 3320 E – Inserting tools.

Standard equipment: Hose coupling with nozzle and nipple · Set of torque adjustment tools · Set of clutch springs

Technical Data

Screwdriver style			Motor size 4	
reversible, trigger-start upper air-inlet, lower air-inlet or rear air-inlet	type order no.		344-347 U 400320 D	344-447 U 400320 E
reversible, push-to-start upper air-inlet, lower air-inlet or rear air-inlet	type order no.		344-349 U 411448 D	344-449 U 411448 E
screws	up to		M5	M6
torque min.	Nm / in.lbs		3.5 / 31	3.5 / 31
torque (soft pull-up) max.	Nm / in.lbs		6.5 / 57.5	8 / 70.8
torque (hard pull-up) max.	Nm / in.lbs		8.5 / 75.2	10 / 88.5
speed, idling	rpm		2400	1700
air consumption	m ³ / min / cfm		1 / 35.3	1 / 35.3
distance from spindle centre to side	mm / in.		21 / 0.8	21 / 0.8
length	mm / in.		292 / 11.4	292 / 11.4
weight	kg / lbs		1.7 / 3.7	1.7 / 3.7
noise level	dB(A)		79	79

Performance data relate to an air pressure of 6.3 bar (90 PSI), Air hose dia. 10 mm/1/4", Internal hex. drive DIN 3126 – F6.3 (1/4"), integrated quick change chuck

Suitable tool inserts and connecting components with a drive as per DIN 3126 E6.3 (1/4"), see also in our brochure D 3320 E – Inserting tools.

Standard equipment: Hose coupling with nozzle and nipple · Set of torque adjustment tools · Set of clutch springs
--

Optional equipment:		Motor size 2	Motor size 2.5	Motor size 3	Motor size 4
Spring-Sleeve cpl., without screw suction	order no.	364672 A	364680 A	364672 A	364672 A
Spring-Sleeve cpl., with screw suction (in connection with finder; see leaflet: Inserting Tools D 3320 E)	order no.	364672 C	364680 D	364672 C	364672 C
Exhaust hose (0.75 m / 2.5 ft.) with air hose (2 m / 6.6 ft.)	order no.	330628 A	330628 A	413417 A	413417 A
handle	order no.	–	–	410 971	410971

DEPRAG

DEPRAG SCHULZ GMBH u. CO.

P.O. Box 1352, D-92203 Amberg, Germany
Kurfürstenring 12-18, D-92224 Amberg
Phone (0 96 21) 371-0, Fax (0 96 21) 371-120
www.deprag.com
info@deprag.de



CERTIFIED AS PER DIN EN ISO 9001
