


Propeller Type Water Meter

Model : WR



6 digits

- Media : Clear Water 、 Wasted Water (Strainer required)
- Temperature : max. 50°C
- Protection : IP65
- Specification :
- Calibration Tolerance : $\pm 2\%$
- Smallest Scale : 0.005M³

Nominal Size (m/m)	Length (mm)	Flow-Rate Range M ³ /Hr			
		Starting flow-rate	Minimum flow-rate ($\pm 2\%$)	Permanent flow-rate ($\pm 2\%$)	Overload flow-rate ($\pm 2\%$)
100 (4")	250	1	8	60	120

When the meter needs to be fixed up, it's not necessary to disassemble all the meter from the pipe, it only needs to take off the upper part of the meter.

Type ex. : WR100 - FCD - F0

Model	Code			Description
WR				6 digits Mechanical Totalizer
Size (mm)	100			100mm (4")
Material	-FCD			Body : Ductile Iron , Vane Wheel : Engineering Plastic.
	-S1			Body : SCS13 , Vane Wheel : Engineering Plastic.
Connection		-F0		JIS 10K FLANGE
		-F1		ANSI 150LB FLANGE

※.The above specifications will be revised any time without prior notification.



SHIN YUAN PRECISION MACHINERY CO.,LTD

No.15, Ln. 393, Fude 1st Rd., Sijhih Dist., New Taipei City 22149, Taiwan

TEL:886-2-26957966

FAX:886-2-26957956

Web site:www.sypm.com.tw

E-Mail: sypm@ms32.hinet.net

CATALOG NO.2017-31