



CHAIN NO.	Pitch		Width	Roller	Plate			Pin			Allowable Load kgf(max)
	P		W	Dia	Height	Thickness		Dia	Lenght		
	inch	mm	(min)	R(max)	H(max)	T1	T2	D(max)	±DH	L	
A2040SS	1"	25.40	7.85	7.92	12.0	1.50	1.50	3.98	9.52	16.72	45
A2050SS	1-1/4"	31.75	9.40	10.16	15.0	2.00	2.00	5.09	11.91	20.96	70
C2040SS	1"	25.40	7.85	7.92	12.0	1.50	1.50	3.98	9.52	16.72	45
C2042SS	1"	25.40	7.85	15.88	12.0	1.50	1.50	3.98	9.52	16.72	45
C2050SS	1-1/4"	31.75	9.40	10.16	15.0	2.00	2.00	5.09	11.91	20.96	70
C2052SS	1-1/4"	31.75	9.40	19.05	15.0	2.00	2.00	5.09	11.91	20.96	70
C2060HSS	1-1/2"	38.10	12.57	11.91	18.0	3.20	3.20	5.96	14.27	27.07	105
C2062HSS	1-1/2"	38.10	12.57	22.23	18.0	3.20	3.20	5.96	14.27	27.07	105
C2080HSS	2"	50.80	15.75	15.88	24.10	4.00	4.00	7.94	19.05	35.18	180
C2082HSS	2"	50.80	15.75	28.58	24.10	4.00	4.00	7.94	19.05	35.18	180

DH length(Pin extension)per requested

Note : AISI 304 chain is with slightly magnetic due to cold forming of parts.