

S DISPENSERS SELF SERVICE MC 2.0 for AdBlue®

EN. The MC 2.0 Self Service non-commercial for AdBlue® fuel dispenser is designed and built for compatibility with the new Self Service Management 2.0 software.

After connecting the dispenser via LAN or WiFi to the 2.0 software, it can be configured directly from a PC: set the parameters, enable the user keys and vehicle keys having access to the dispenser, and constantly receive and transmit data for the generation of reports.

Sturdy structure fitted with front panel for easy maintenance.

Diaphragm pump is equipped with an electric motor that has no need for a dynamic seal. This solution forms the basis for the production of a reliable industrial pump with self-priming capabilities. The Self Service MC also comes with our SB325 automatic nozzle with break-away system and stainless steel spout and the AdBlue® 3D Filter.

ES. El surtidor para AdBlue® para uso privado Self Service MC 2.0 es específicamente compatible con el nuevo software Self Service Management 2.0.

Una vez conectado por LAN o wifi al software 2.0, el surtidor se configura totalmente desde el ordenador, se pueden ajustar los parámetros, habilitar las llaves de los usuarios y vehículos que tienen acceso al surtidor e intercambiar datos continuamente para generar informes.

Estructura robusta con puerta frontal para facilitar el mantenimiento. Bomba de membrana dotada de motor eléctrico sin juntas dinámicas. Esta solución permite obtener una bomba industrial fiable y autocebante. Pistola automática SB325 con sistema Break-Away y caño de acero inoxidable. FILTRO 3D para AdBlue®.

RU. Раздаточная колонка для дизельного топлива Self Service MC 2.0 предназначена для выполнения частных заправочных операций и совместима с новым программным обеспечением Self Service Management 2.0. Колонку можно подключить по сети LAN или WiFi к программному обеспечению 2.0 и настраивать прямо с персонального компьютера: задавать параметры, активировать ключи пользователей и транспортных средств для доступа к колонке, непрерывно получать и отправлять данные для составления отчетов.

Прочная конструкция, оснащенная передним окошком для упрощения техобслуживания. Мембранный насос с электромотором без динамических уплотнений.

Это решение позволяет создать надежный промышленный насос с возможностью самозаливки. Автоматический пистолет SB325 с разрывной муфтой и носиком из нержавеющей стали. Трехмерный фильтр для AdBlue®.

PERFORMANCE


- Flow rate up to 34 l/min
- Accuracy: +/- 0.5 %
- Continuous AC operation.
- Noise level below 75 dB
- IP55 Protection
- LAN adapter

- Caudal de hasta 34 l/min
- Precisión: +/- 0.5 %
- Funcionamiento CA continuo
- Nivel de ruido inferior a 75 dB
- Protección IP55
- LAN adapter

- Расход до 34 л/мин
- Погрешность измерения: +/- 0.5 %
- Непрерывное функционирование от электросети
- Уровень шума ниже 75 дБ
- Защита IP55
- адаптер локальной сети

DIMENSIONS

COLUMN
VERSION



Hose:
- length 6 m
- Ø 3/4"

PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		N. Boxes/ Europallet	
	kg	lbs	mm	pcs/ box		
Column versions						
F00743060	50	110	1478x488x400	1	6*	4

* Pallet XL

DISPENSERS



Flow-rate
up to
34 l/min
(up to 9 gpm)

Accuracy
+/-
1 %

Required
Self Service
Management
2.0



PIUSI

DISPENSERS

PUMPS

METERS

NOZZLE
METERS

NOZZLE

SPECIAL
EQUIPMENTS

FLUID
MONITORING

HOSE
REEL

FILTERING


ACCESSORIES



EXISTING LAN NETWORK



WIFI (ON REQUEST)



MAGNETIC KEY (ON REQUEST)



SELF SERVICE[®]
MANAGEMENT 2.0


REQUIRED

FEATURES

ON REQUEST



Code F00611D10



Code **F15904000**
(10 pcs)



Code **F17299000**
(10 pcs)



Code **F12710120**



Code **F12710090**
An hot spot and
repeater in case of
long distance

PRODUCTS' RANGE TECHNICAL DATA

TECHNICAL DATA													
Code	Description	Fluids	Flow-rate		Voltage			Meter	Nozzle	Filter	Inlet	Self Service Management 2.0	
		type	l/min	gpm	AC V/Hz DC Volt	Power Watt	Amp. max.	mod.	type	3D filter	BSP		
Column versions													
F00743060	Self service 70 MC 2.0 for AdBlue®		34	9	230/50	400	1,95	K24	SB325	YES	3/4"		required