



Description & Features:

- Economical 4.5" (115mm) stainless steel case gauge
- $\pm 1\%$ accuracy
- Zero adjustment screw
- $\frac{1}{4}$ " NPT
- CRN registered
- 3 year warranty

Applications:

- Most commercial air, water and steam services that require a $\pm 1\%$ full-scale accuracy

Specifications	
Dial	4.5" (115mm) white aluminum dial with black and red markings
Case	304 SS
Lens	Acrylic
Ring	304 SS
Socket	Brass
Connection	$\frac{1}{4}$ " NPT standard
Bourdon Tube	Phosphor bronze
Movement	Brass
Pointer	Aluminum, anodized black, recalibrator screw
Welding	Silver solder
Over-Pressure Limit	25% for pressures up to 1,400 psi (9,653 kPa) 15% for pressures over 1,400 psi (9,653 kPa)
Working Pressure	Maximum 75% of full scale value
Ambient/Process Temperature	-40°F to 150°F (-40°C to 65°C)
Accuracy	$\pm 1\%$ ANSI/ASME Grade 1A
Enclosure Rating	IP52

Order Codes (products in bold are normally in stock)

Connection	$\frac{1}{4}$ Bottom
30" Hg. vacuum/kPa	PCT320
30"/0/30 psi/kPa	PCT329
30"/0/60 psi/kPa	PCT330
30"/0/100 psi/kPa	PCT328
30"/0/160 psi/kPa	PCT332
30"/0/200 psi/kPa	PCT333
30"/0/300 psi/kPa	PCT334
0 - 15 psi/kPa	PCT319
0 - 30 psi/kPa	PCT321
0 - 60 psi/kPa	PCT322
0 - 100 psi/kPa	PCT323
0 - 160 psi/kPa	PCT324
0 - 200 psi/kPa	PCT325
0 - 300 psi/kPa	PCT326
0 - 400 psi/kPa	PCT327
0 - 600 psi/kPa	PCT331
0 - 1,000 psi/kPa	PCT293
0 - 3,000 psi/kPa	PCT294
0 - 5,000 psi/kPa	PCT295



Tel: 1-800-WINTERS / www.winters.com