

深溝滾珠軸承

主要寸法(mm)				型 號	基本定格荷重(kgf)	
d	D	B	r		C 動荷重	Co 靜荷重
10	19	5	0.5	6800zz	135	75
	22	6	0.5	6900zz	212	117
	26	8	0.5	6000zz	360	196
	30	9	1	6200zz	400	229
	35	11	1	6300zz	635	365
12	21	5	0.5	6801zz	150	91
	24	6	2.5	6901zz	227	133
	28	7	0.5	16001	400	229
	28	8	0.5	6001zz	400	229
	32	10	1	6201zz	535	305
	37	12	1.5	6301zz	760	450
	15	24	5	0.5	6802zz	163
28		7	0.5	6902zz	340	205
32		8	0.5	16002	440	263
32		9	0.5	6002zz	440	263
35		11	1	6202zz	600	360
42		13	1.5	6302zz	895	545
17	26	5	0.5	6803zz	206	135
	30	7	0.5	6903zz	360	228
	35	8	0.5	16003	470	296
	35	10	0.5	6003zz	470	296
	40	12	1	6203zz	750	460
	47	14	1.5	6303zz	1070	660
20	32	7	0.5	6804zz	273	191
	37	9	0.5	6904zz	500	330
	42	8	0.5	16004	620	405
	42	12	1	6004zz	735	465
	47	14	1.5	6204zz	1000	635
	52	15	2	6304zz	1250	785
22	44	12	1	60/22zz	740	40
	50	14	1.5	62/22zz	1010	645
	56	16	2	63/22zz	1440	920

深溝滾珠軸承

主要寸法(mm)				型 號	基本定格荷重(kgf)	
d	D	B	r		C 動荷重	Co 靜荷重
25	37	7	0.5	6805zz	300	234
	42	9	0.5	6905zz	550	395
	47	8	0.5	16005	695	490
	47	12	1	6005zz	790	525
	52	15	1.5	6205zz	1100	730
	62	17	2	6305zz	1610	1080
28	52	12	1	60/28zz	975	665
	58	16	1.5	62/28zz	1310	885
	68	18	2	63/28zz	2100	1400
30	42	7	0.5	6806zz	355	285
	47	9	0.5	6906zz	570	430
	55	9	0.5	16006	880	645
	55	13	1.5	6006zz	1030	740
	62	16	1.5	6206zz	1530	1050
	72	19	2	6306zz	2090	1440
32	58	13	1.5	60/32zz	1180	825
	65	17	105	62/32zz	1630	1090
	75	20	2	63/32zz	2340	1630
35	47	7	0.5	6807zz	370	320
	55	10	1	6907zz	815	620
	62	9	0.5	16007	960	760
	62	14	1.5	6007zz	1250	915
	72	17	2	6207zz	2010	1430
	80	21	2.5	6307zz	2620	1840
40	52	7	0.5	6808zz	345	335
	62	12	1	6908zz	1070	855
	68	9	0.5	16008	1020	875
	68	15	1.5	6008zz	1310	1010
	80	18	2	6208zz	2280	1650
	90	23	2.5	6308zz	3200	2300

深溝滾珠軸承

主要寸法(mm)				型 號	基本定格荷重(kgf)	
d	D	B	r		C 動荷重	Co 靜荷重
45	58	7	0.5	6809zz	500	480
	68	12	1	6909zz	1110	95
	75	10	1	16009	1170	965
	75	16	1.5	6009zz	1640	1320
	85	19	2	6209zz	2570	1880
	100	25	2.5	6309zz	4150	3100
50	65	7	0.5	6810zz	515	525
	72	12	1	6910zz	1140	990
	80	10	1	16010	1250	1110
	80	16	1.5	6010zz	1710	1430
	90	20	2	6210zz	2750	2100
	110	27	3	6310zz	4850	3650
55	72	9	0.5	6811zz	770	690
	80	13	1.5	6911zz	1250	1110
	90	11	1	16011	1520	1370
	90	18	2	6011zz	2220	1850
	100	21	2.5	6211zz	3400	2660
	120	29	3	6311zz	5600	4330
60	78	10	0.5	6812zz	900	895
	85	13	1.5	6912zz	1520	1370
	95	11	1	16012	1570	1460
	95	18	2	6012zz	2310	200
	110	22	2.5	6212zz	4100	3300
	130	31	3.5	6312zz	6400	5000
65	85	10	1	6813zz	935	985
	90	13	1.5	6913zz	1360	1330
	100	11	1	16013	1610	1550
	100	18	2	6013zz	2400	2150
	120	23	2.5	6213zz	4500	3650
	140	33	3.5	6313zz	7250	5750

深溝滾珠軸承

主要寸法(mm)				型 號	基本定格荷重(kgf)	
d	D	B	r		C 動荷重	Co 靜荷重
70	90	10	1	6814zz	950	1030
	100	16	1.5	6914zz	1860	1770
	110	13	1	16014	2180	210
	110	20	2	6014zz	2980	2660
	125	24	2.5	6214zz	4900	4000
	150	35	3.5	6314zz	8150	6550
75	95	10	1	6815zz	985	1120
	105	16	1.5	6915zz	1910	1880
	115	13	1	16015	2180	2110
	115	20	2	6015zz	3100	2870
	130	25	2.5	6215zz	5150	4400
	160	37	3.5	6315zz	8900	7400
80	100	10	1	6816zz	990	1160
	110	16	1.5	6916zz	1950	1990
	125	14	1	16016	2500	2470
	125	22	2	6016zz	3750	3400
	140	26	3	6216zz	5700	4750
	170	39	3.5	6316zz	9650	8300
85	110	13	1.5	6817zz	1470	1630
	120	18	2	6917zz	2500	2470
	130	14	1.5	16017	2570	2630
	130	22	2.5	6017zz	3900	3700
	150	28	3	6217zz	6600	5600
	180	41	4	6317zz	10400	9250
90	115	13	1.5	6818zz	1490	1700
	125	18	2	6918zz	2570	2630
	140	16	1.5	16018	3250	3300
	140	24	2.5	6018zz	4550	4300
	160	32	3.5	6218zz	7550	6450
	190	45	4	6318zz	11200	10200

深溝滾珠軸承

主要寸法(mm)				型 號	基本定格荷重(kgf)	
d	D	B	r		C 動荷重	Co 靜荷重
95	120	13	1.5	6819zz	1510	1780
	130	18	2	6919zz	2640	2780
	145	16	1.5	16019	3350	3500
	145	24	2.5	6019zz	4750	4600
	170	32	3.5	6219zz	8550	7400
	100	45	4	6319zz	12000	11300
100	125	13	1.5	6820zz	1530	1850
	140	20	2	6920zz	3400	3500
	150	16	1.5	16020	3400	3700
	150	24	2.5	6020zz	4750	4900
	180	34	3.5	6220zz	9600	8450
	215	47	4	6320zz	13600	13500
105	130	13	1.5	6821zz	1560	1930
	145	20	2	6921zz	3300	3500
	160	18	1.5	16021	4050	4250
	160	26	3	6021zz	4700	5600
	190	36	3.5	6221zz	10400	9500
	225	49	4	6321zz	14400	14700
110	140	16	1.5	6822zz	2490	2890
	150	20	2	6922zz	3400	3700
	170	19	1.5	16022	4500	4750
	170	28	3	6022zz	6650	6250
	200	38	3.5	6222zz	11300	10600
	240	50	4	6322zz	16100	17200
120	150	16	1.5	6824zz	2510	3050
	165	22	2	6924zz	4150	4500
	180	19	1.5	16024	4750	5350
	180	28	3	6024zz	6900	6850
	215	40	3.5	6224zz	12200	11990
	260	55	4	6324zz	16200	17400

深溝滾珠軸承

主要寸法(mm)				型 號	基本定格荷重(kgf)	
d	D	B	r		C 動荷重	Co 靜荷重
130	165	18	2	6826zz	2890	3550
	180	24	2.5	6926zz	5100	5600
	200	22	2	16026	5950	6450
	200	33	3	6026zz	8300	8600
	230	40	4	6226zz	13000	13200
	280	58	5	6326zz	18000	23200
140	175	18	2	6828zz	2920	3700
	190	24	2.5	6928zz	5250	5950
	210	22	2	16028	6100	6850
	210	33	3	6028zz	8650	9200
	250	42	4	6228zz	13000	13300
	300	62	5	6328zz	19800	23200
150	190	20	2	6830zz	3750	4750
	210	28	3	6930zz	6650	7500
	225	24	2	16030	6800	7950
	225	35	3.5	6030zz	9800	10400
	270	45	4	6230zz	13700	14700
	320	65	5	6330zz	21600	26300
160	200	20	2	6832zz	3800	4950
	220	28	3	6932zz	6550	7550
	240	25	2.5	16032	7550	8950
	240	38	3.5	6032zz	10700	11500
	290	48	4	6232zz	14500	16200
	340	68	5	6332zz	21800	26600
170	215	22	2	6834zz	4700	6050
	230	28	3	6934zz	6750	8000
	260	28	2.5	16034	8950	10500
	260	42	3.5	6034zz	12600	13700
	310	52	5	6234zz	16600	19500
	360	72	5	6334zz	25600	33500

深溝滾珠軸承

主要寸法(mm)				型 號	基本定格荷重(kgf)	
d	D	B	r		C 動荷重	Co 靜荷重
180	225	22	2	6836zz	4750	6350
	250	33	3	6935zz	8600	9950
	280	31	3	16036	11300	13200
	280	46	3.5	6036zz	14100	15900
	320	52	5	6236zz	17700	21200
	380	75	5	6336zz	27800	38000
190	240	24	2.5	6838zz	5750	7600
	260	33	3	6938zz	8850	13200
	290	31	3	16038	11700	15900
	290	46	3.5	6038zz	14700	19400
	340	55	5	6238zz	19900	27200
	400	78	6	6338zz	27800	41500
200	250	24	2.5	6840zz	5800	7900
	280	38	3.5	6940zz	11200	13200
	310	34	3	16040	13100	15900
	310	51	3.5	6040zz	16200	19400
	360	58	5	6240zz	21000	27200
	420	80	6	6340zz	29700	41500
220	270	24	2.5	6844zz	6000	8500
	300	38	3.5	6944zz	11500	14000
	340	37	3.5	16044	14100	18100
	340	56	4	6044zz	18400	23300
	400	65	5	6244zz	24300	33000
240	300	28	3	6848zz	7700	11000
	320	38	3.5	6948zz	12100	15600
	360	37	3.5	16048	15300	20100
	360	56	4	6048zz	19200	25200
	440	72	5	6248zz	26500	38000